



# Technical Data Sheet: SU324

<b>Product manual</b>	<p><b>SU324</b> is a modified epoxy acrylate oligomer. It has high reactivity, good leveling and fullness, good yellow resistance. It is suitable for plastic coatings, wood coatings, Cosmetic coatings etc.</p>	
<b>Product features</b>	<p>Good pigment wetting</p> <p>Good leveling and fullness</p> <p>Good yellow resistance</p>	
<b>Recommended use</b>	<p>Wood coating</p> <p>3C coating</p>	
<b>Specifications</b>	Functionality (theoretical)	2
	Appearance (By vision)	Clear liquid
	Viscosity (CPS/60°C)	1200-2600
	Color (Gardner)	≤2
	Efficient content (%)	100
<b>Packing</b>	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
<b>Storage conditions</b>	<p>Please keep cool or dry place, and avoid sun and heat;</p> <p>Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.</p>	
<b>Use matters</b>	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	