



Technical Data Sheet: CR90843

Product manual	<p>CR90843 is a 9-functional aromatic polyurethane acrylate oligomer; it has the characteristics of fast curing speed, excellent abrasion resistance, high hardness, good leveling, excellent adhesion, and good vibration and abrasion resistance; It is especially suitable for 3C plastic coatings, cosmetics and mobile phone vacuum electroplating top coatings, wood coatings and other application fields.</p>	
Product features	<p>High hardness</p> <p>Good vibration and wear resistance</p> <p>Good toughness</p> <p>Good leveling</p>	
Recommended use	<p>Plastic coatings</p> <p>Vacuum plating topcoat</p> <p>Wood coatings</p>	
Specifications	Functionality (theoretical)	9
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	1500-3500
	Color(Gardner)	≤1
	Efficient content(%)	100
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum</p>	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	