



## Technical Data Sheet: HT7600

Product manual	<p><b>HT7600</b> is a polyester acrylate oligomer which developed for UV/EB-cured coatings and inks. It has fast curing speed , surface-dry easily, low distinct viscosity, good gloss retention, good adhesion, compared to similar products on the market, and it is high hardness, good abrasion resistance, smell small and low distinct viscosity.It is suitable used on plastic coating , wood coating ,OPV ,metal coating and so on.</p>	
Product features	<p>Low distinct viscosity                  Very fast cure                  Good adhesion                  Good hardness &amp; toughness                  Good weatherability                  High Abrasion Resistance</p>	
Suggested application	<p>Coatings                  Bamboo flooring                  PVC floor tile                  Plastic spraying</p>	
Specifications	Functional basis (theoretical)	6
	Appearance(By vision)	Little yellow liquid
	Viscosity (CPS/25℃)	1400-2600
	Color (Gardner)	≤ 1
	Efficient content(%)	100
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
Storage conditions	<p>Resin please keep cool or dry place, and avoid sun and heat;                  Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate;                  for details, please refer to the Material Safety Instructions (MSDS);                  Each batch of goods to be tested before they can be put into production</p>	