



Technical Data Sheet: 0038F

Product manual	<p>0038F is a polyurethane acrylate ;It provides self matting property , fast curing speed, good scratch resistance and high transmittance.It is suitable for UV matting coating on plastic,wood ,paper and so on.</p>	
Product features	<p>High matting efficiency</p> <p>Fast curing speed</p> <p>Good wetting on substrate</p> <p>Good scratch resistance</p>	
Recommended use	<p>UV plastic coating</p> <p>UV wood coating</p> <p>OPV</p>	
Specifications	<p>Functional basis (theoretical)</p> <p>Appearance(By vision)</p> <p>Viscosity (CPS/25℃)</p> <p>Color(Gardner)</p> <p>Efficient content(%)</p>	<p>4</p> <p>Little yellow liquid</p> <p>2,000-6,000</p> <p>≤1</p> <p>100</p>
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat;</p> <p>Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	