



Technical Data Sheet: CR90512

Product manual	<p>CR90512 is a polyurethane acrylate oligomer. it has the characteristics of fast curing speed, good adhesion, and good snow effect. it is mainly used in the fields of plastic coating and screen ink.</p>	
Product features	<p>Fast curing speed</p> <p>Good snow effect</p> <p>Wrinkle fast</p>	
Recommended use	<p>Plastic coating</p> <p>Screen ink</p>	
Specifications	Functionality (theoretical)	2
	Appearance(By vision)	Clear &Clean liquid
	Viscosity (CPS/25℃)	42000-78000
	Color(APHA)	≤100
	Efficient content(%)	100
Packing	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum.</p>	
Storage conditions	<p>Please keep cool or dry place, and avoid sun and heat;</p> <p>Storage temperature does not exceed 40 °C , storage conditions under normal conditions for at least 6 months.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	