



## Technical Data Sheet: CR90051

<b>Product manual</b>	<b>CR90051</b> is a urethane acrylate oligomer. It has good leveling, good wetting, perfect adhesion on plastic substrates ; It is suitable for UV plastic coatings , vacuum coatings and wood coatings.	
<b>Product features</b>	Perfect adhesion Good wetting Good fullness	
<b>Suggested application</b>	Plastic coatings Vacuum coatings(primer&topcoat) Hard to adhesion substrate application	
<b>Specifications</b>	Functional basis (theoretical)	3
	Appearance(By vision)	Little yellow liquid
	Viscosity(CPS/25℃)	300-800
	Color (Gardner)	≤ 1
	Efficient content(%)	100
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	