



# Technical Data Sheet: CR90704

<b>Product manual</b>	CR90704 is a water-based UV aliphatic polyurethane acrylate dispersion, which has the characteristics of fast curing speed, high hardness, good flexibility, good adhesion, and good solvent resistance. It is suitable for wood coatings, plastic coatings, etc.	
<b>Product features</b>	Fast curing speed High hardness Good flexibility Good adhesion Good solvent resistance	
<b>Recommended use</b>	Wood coating Plastic coating	
<b>Specifications</b>	Functionality (theoretical)	2
	Appearance(By vision)	Milky white translucent liquid, with blue light
	Viscosity (CPS/25℃)	10-200
	PH	5.5-6.5
	Efficient content(%)	38-40
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	