



# Technical Data Sheet: CR90791

<b>Product manual</b>	CR90791 is an aliphatic polyurethane acrylate oligomer with good flexibility, good adhesion, good leveling and easily metalized. It is widely used in plastic coatings, vacuum plating primer, screen ink and other fields.	
<b>Product features</b>	Good flexibility Fast curing speed Good adhesion Good leveling High gloss	
<b>Recommended use</b>	Plastic coatings Vacuum plating primer Adhesives Screen ink	
<b>Specifications</b>	Functionality (theoretical)	2
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/60℃)	20000-40000
	Color(Gardner)	≤1
	Efficient content(%)	≥99.9
<b>Packing</b>	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
<b>Storage conditions</b>	Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
<b>Use matters</b>	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	