



Technical Data Sheet: CR91000

| | | |
|------------------------------|---|--------------|
| Product manual | CR91000 is a nano-hybrid modified high-functionality polyurethane acrylate oligomer. It has excellent toughness and wear resistance, chemical resistance, scratch resistance and high hardness, and excellent fingerprint resistance. It is especially suitable for hardening liquid. | |
| Product features | Good wear resistance Good chemical resistance High hardness Excellent steel wool resistance 3000-5000 times | |
| Suggested application | Mobile phone coatings 3C coatings | |
| Specifications | Functional basis (theoretical) | 10 |
| | Appearance(By vision) | Milky liquid |
| | Viscosity(CPS/25℃) | 700-1600 |
| | Efficient content(%) | 85±5 |
| Packing | Net weight 50KG plastic bucket and net weight 200KG iron drum | |
| Storage conditions | Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months. | |
| Use matters | Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production. | |