



Technical Data Sheet: HE3218P

Product manual	HE3218P is a bifunctional epoxy acrylate; it has good flexibility in UV/EB curing coatings, inks and adhesives, it has good balance of water and ink, good adhesion, good pigment wetting, low shrinkage, fast curing speed, and good chemical resistance, and it has high gloss and abrasion resistance.	
Product features	Good pigment wetting Good flexibility Good abrasion resistance and pollution resistance High gloss, high reactivity	
Suggested application	Offset ink Flexible substrate primer and top coat Adhesives, laminating technology Metal, plastic, floor, paper, wood coatings	
Specifications	Functional basis (theoretical)	2
	Appearance(By vision)	yellow liquid
	Viscosity (CPS/60℃)	2000-4000
	Color (APHA)	≤ 300
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
Storage conditions	Resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months.	
Use matters	Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.	