



Technical Data Sheet: HT7004

Product manual	HT7004 is a Polyester acrylate oligomer, it has excellent adhesion, resistance to water, acid.	
Product features	<ul style="list-style-type: none"> Low energy curing Adhesion Flexibility Low Shrinkage Water Resistance Weatherability 	
Suggested application	<ul style="list-style-type: none"> Coatings Inks Nail polish 	
Specifications	Functional basis (theoretical)	1.5
	Appearance(By vision)	Little yellow liquid
	Viscosity(CPS/65°C)	6000-12000
	Color (APHA)	≤ 100
	Efficient content(%)	100
Packing	Net weight 50KG plastic bucket and net weight 200KG iron drum.	
Storage conditions	<p>Store product indoors at temperatures greater than product's freezing point (or greater than 0C/32F if no freezing point available) and below 38C/100F. Avoid prolonged (longer than shelf-life) storage temperatures above 38C/100F. Store in tightly closed containers in a properly vented storage area away from: heat, sparks, open flame, strong oxidizers, radiation, and other initiators. Prevent contamination by foreign materials. Prevent moisture contact. Use only non-sparking tools and limit storage time. Unless specified elsewhere, shelf-life is 6 months from receipt.</p>	
Use matters	<p>Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production.</p>	