



Technical Data Sheet: H220

| | | |
|---------------------------|--|--------------|
| Product manual | H220 is a two-functional polyester acrylate oligomer; it has the characteristics of good adhesion, good leveling, high flexibility, ultra-low viscosity, good dilution, and high cost performance. It is mainly used in wood UV, paper UV, and plastic overprint UV. It can also partially replace TPGDA. | |
| Product features | Excellent leveling Good fullness Good flexibility High solid and low viscosity | |
| Recommended use | Wood UV Paper UV | |
| Specifications | Functionality (theoretical) | 2 |
| | Appearance(By vision) | Clear liquid |
| | Viscosity (CPS/25℃) | 30-70 |
| | Color(Gardner) | ≤2 |
| | Efficient content(%) | 100 |
| Packing | Net weight 50KG plastic bucket and net weight 200KG iron drum | |
| Storage conditions | Please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months. | |
| Use matters | Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production. | |