



Technical Data Sheet: HP6400

| | | |
|------------------------------|--|----------------------|
| Product manual | HP6400 is a urethane acrylate oligomer that defers superior physical properties such as curing speed fast, surface-dry easily, non-yellowing, good gloss retention, good anti-cracking performance, good adhesion. Compared to similar products on the market, significant feature is high hardness, distinct low viscosity, good abrasion resistance, smell small and non-yellowing. | |
| Product features | Excellent adhesion Chemical Resistance Good hardness. Water Resistance Weatherability Fast curing speed | |
| Suggested application | Coatings Inks | |
| Specifications | Functional basis (theoretical) | 6 |
| | Appearance(By vision) | Little yellow liquid |
| | Viscosity (CPS/60℃) | 2400-6600 |
| | Color (Garder) | ≤1 |
| | Efficient content(%) | 100 |
| Packing | Net weight 50KG plastic bucket and net weight 200KG iron drum | |
| Storage conditions | resin please keep cool or dry place, and avoid sun and heat; Storage temperature does not exceed 40 ℃, storage conditions under normal conditions for at least 6 months. | |
| Use matters | Avoid touching the skin and clothing, wear protective gloves when handling; Leak with a cloth when the leak, and wash with ethyl acetate; for details, please refer to the Material Safety Instructions (MSDS); Each batch of goods to be tested before they can be put into production. | |