



# Technical Data Sheet: HU9455

<b>Product manual</b>	<p><b>HU9455</b> is a reactive tertiary amine co-initiator. It can provide very fast surface cure to overcome the oxygen-inhibited problem when in combination with benzophenone type photoinitiator. It is suitable for paper varnish, screen and flexo printing, wood, plastic coatings and other fields.</p>	
<b>Product features</b>	<p>Fast cure speed, especially at the surface</p> <p>Light color</p> <p>Good stability</p> <p>High Gloss</p>	
<b>Recommended use</b>	<p>Coatings</p> <p>Inks</p>	
<b>Specifications</b>	<p>Appearance(By vision)</p> <p>Viscosity (cps/25°C)</p> <p>Color(APHA)</p> <p>Efficient content(%)</p>	<p>Clear liquid</p> <p>50-100</p> <p>≤500</p> <p>100</p>
<b>Packing</b>	<p>Net weight 50KG plastic bucket and net weight 200KG iron drum</p>	
<b>Storage conditions</b>	<p>Please keep cool or dry place, and avoid sun and heat;</p> <p>Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.</p>	
<b>Use matters</b>	<p>Avoid touching the skin and clothing, wear protective gloves when handling;</p> <p>Leak with a cloth when the leak, and wash with ethyl acetate;</p> <p>for details, please refer to the Material Safety Instructions (MSDS);</p> <p>Each batch of goods to be tested before they can be put into production.</p>	