



Technical Data Sheet: CR91978

Product manual **CR91978** is a four-functional modified polyester acrylate; It has the characteristics of high reactivity, high hardness, good scratch resistance, good toughness, good boiling water resistance, outstanding yellowing resistance, and high cost performance. It is especially suitable for plastic coating, cosmetics and mobile phone vacuum plating topcoat, wood coating and screen ink and other fields.

Product features

- High reactivity
- High hardness
- Good yellowing resistance
- Good toughness

Recommended use

- Plastic coating
- Cosmetic vacuum plating finish
- Wood coating
- Ink

Specifications	Functionality (theoretical)	4
	Appearance(By vision)	Clear liquid
	Viscosity (CPS/25℃)	3000-7000
	Color(Gardner)	≤1
	Efficient content(%)	≥99

Packing Net weight 50KG plastic bucket and net weight 200KG iron drum.

Storage conditions Please keep cool or dry place, and avoid sun and heat;
Storage temperature does not exceed 40 °C, storage conditions under normal conditions for at least 6 months.

Use matters

Avoid touching the skin and clothing, wear protective gloves when handling;
Leak with a cloth when the leak, and wash with ethyl acetate;
for details, please refer to the Material Safety Instructions (MSDS);
Each batch of goods to be tested before they can be put into production.